

SIRIM QAS International Sdn. Bhd.

No. 1, Persiaran Dato' Menteri, P.O.Box 7035, Seksyen 2, 40700 Shah Alam, Selangor Darul Ehist

MALAYSIA Tel: 03-55446465 (Company No: 410334-X)

Fax: 03-55446454

http://www.sirim.my



SAMM NO. 231

TEST REPORT

REPORT NO.:

2015FE0240

PAGE

OF

4

This Test Report refers only to samples submitted by the applicant to SIRIM QAS International Sdn. Bhd. and tested by SIRIM QAS International Sdn. Bhd. This Test Report shall not be reproduced, except in full and shall not be used for any purpose by any means or forms (including but not limited to advertising purposes) without written approval from the Managing Director, SIRIM QAS International Sdn. Bhd. Please refer overleaf of Page 1 for Conditions Relating to the Use of Test Report.

Applicant/

EASY WOOD SDN. BHD.

Manufacturer

No. 4, Jalan BP 5/8, Bandar Bukit Puchong, 47100 Puchong, Selangor Darul Ehsan.

(Attn: Mr. Ben Fok / Mr. Mike Ng)

Product

EAZY WOOD TONGUE AND GROOVE CEILING STRIP

Reference Standard/

BS 476 : Part 7: 1997

Method of Test

Fire Test on Building Materials and Structures

Part 7: Surface Spread of Flame Test.

Description of Test

Specimen

6 pieces of Eazy Wood Tongue And Groove Ceiling Strip.

Size of Specimen

270mm × 885mm × thickness (Refer to page 2)

Brand

EAZY WOOD

Mass Per Unit Area

4.18 kg/m²

Descriptions of sample as claimed by the submitter: Refer to page 2

The specimens were tested with the face side exposed to the specified heating

condition of the fire test.

Date Received

18.03.2015

Date of Test

07.04.2015

Job No./ Ref No.

J20151440117 /SQAS/FPS/15/1-6

Test Result

Classification of Surface Spread of Flame Test

Class 1(Y

Issued Date

1 1 MAY 2015

Approved Signatories

HANAFI MOHAMAD Senior Testing Executive FIRE PROTECTION SECTION SECTION

ROHAYA IBRAHIM Head


Fire Protection Section
Testing Services Department
SIRIM QAS International Sdn. Bhd.

REPORT NO.: 2015FE0240

PAGE 2 OF 4

This Test Report refers only to samples submitted by the applicant to SIRIM QAS International Sdn. Bhd. and tested by SIRIM QAS International Sdn. Bhd. This Test Report shall not be reproduced, except in full and shall not be used for any purpose by any means or forms (including but not limited to advertising purposes) without written approval from the Managing Director, SIRIM QAS International Sdn. Bhd. Please refer overleaf of Page 1 for Conditions Relating to the Use of Test Report.

Descriptions of sample as claimed by the submitter:



Polymer Composite Tongue and Groove Ceiling Strip



REPORT NO.: 2015FE0240

PAGE 3 OF 4

This Test Report refers only to samples submitted by the applicant to SIRIM QAS International Sdn. Bhd. and tested by SIRIM QAS International Sdn. Bhd. This Test Report shall not be reproduced, except in full and shall not be used for any purpose by any means or forms (including but not limited to advertising purposes) without written approval from the Managing Director, SIRIM QAS International Sdn. Bhd. Please refer overleaf of Page 1 for Conditions Relating to the Use of Test Report.

Name of Applicant

: EASY WOOD SDN. BHD.

Product

: EAZY WOOD TONGUE AND GROOVE CEILING STRIP

Brand

: EAZY WOOD

Mass Per Unit Area

4.18 kg/m²

Date of Test

: 07.04.2015

Requirement

The flame spread on any specimen of the sample shall not exceed the limit assigned for the class with the proviso that for one specimen only in the sample the flame spread may exceed this limit by the tolerance shown.

Classification of Surface Spread of Flame

Classification	Flame Spread at 1½ min		Final Flame Spread		
	Limit (mm)	Tolerance for one specimen in sample (mm)	Limit (mm)	Tolerance for one specimen in sample (mm)	
Class 1	165	25	165	25	
Class 2	215	25	455	45	
Class 3	265	25	710	75	
Class 4		Exceeding Class	3 limits		



11 MAY 2015

REPORT NO.: 2015FE0240 PAGE 4 OF 4

This Test Report refers only to samples submitted by the applicant to SIRIM QAS International Sdn. Bhd. and tested by SIRIM QAS International Sdn. Bhd. This Test Report shall not be reproduced, except in full and shall not be used for any purpose by any means or forms (including but not limited to advertising purposes) without written approval from the Managing Director, SIRIM QAS International Sdn. Bhd. Please refer overleaf of Page 1 for Conditions Relating to the Use of Test Report.

Test Results

Product : EAZY WOOD TONGUE AND GROOVE CEILING STRIP Mass Per Unit Area : 4.18 kg/m²

Brand : EAZY WOOD Date of Test : 07.04.2015

Specimen No.	1	2	3	4	5	6
Spread of flame at 1½ minutes (mm)	0	0	0	0	0	0
Distance (mm)	Time of	spread of fl	(minutes . seconds)			
75	-			1 · · · · · · · · · · · · · · · · · · ·	i de	-
165	-	-	-	- 1	-	-
190		-	-	· ·	, J-	-
215		A . T	-	T - 1		-
240	-	-			-	-
265		7-7-5	-	1 8	•	-
290	-	•	344		7-	-
375		-		-		-
455		Mile A	-	- 1	57 -	-
500	-	F-1112 Ph-11129	-	- 14	-	-
525	-			-	-	-
600	•	() ·	-		S AND THE REST	-
675		-		. v (±. 1)	-	-
710		-			Salat	-
750		-	-	7 J		-
785	-		-	-		ICES DA
825		100	300 to 0.43	90 1007	SER	DES PES
865		1 - 200			13/	- /s
Time of maximum spread of flame (minutes . seconds)		- 1			PRO SE	TECTION E
Distance of maximum spread of flame (mm)	0	0	0	0	0	* 0

Observation

No flaming has been observed. After 5.00 minute all the six specimens shrinked and slumped out of the specimen holder.

Conclusion

In accordance with the class definition specified in the standard, the test results show that the sample tested has a Class One Y (1Y) Surface Spread of Flame as per clause 9.2.3 and clause 11.5 (b).

The test results relate only to the behavior of the test specimens of a product under the particular conditions of test; they are not intended to be sole criterion for assessing the potential fire hazard of the product in use.

